

NovezWeb Glassfibre Netting

DESCRIPTION

NovezWeb Glassfibre Netting is designed to act as a strong reinforcement used in most waterproofing emulsion coating, joints on pre-fabricated panel wall, dry wall, plaster ceiling, and repair of cracks. Compared to the common chopstrains, NovezWeb Glassfibre Netting reduces the constraint of working with loose and inconsistent distribution of strains. Hence, retaining the integrity of materials.

RECOMMENDED USES

- Used as reinforcement in waterproofing emulsion coating and crack repairs

ADVANTAGES

- High strength
- Will not trap air that cause blisters and bubbles
- Easy to handle
- Minimum wastage

TYPICAL PROPERTIES	
Odour and Appearance	Odourless cloth netting
Solubility	Non-soluble netting
Combustibility	Non-combustible
Density (counts per inch)	Warp: 10 x 2 Weft: 10
Gross Weight	Min. 50g per square meter
Minimum Tensile Strength	Warp: 400N per 50mm Weft: 420N per 50mm

PACKING AND COVERAGE

NovezWeb Glassfibre Netting comes in 1m x 100m roll.

Authorized Distributor:

Asia Mortar

Singapore Tel: +65 6269 5575

Malaysia Tel: +60 6 4416 818

Vietnam Tel: +84 8 3820 8686

Whilst every effort is made to ensure that the contents of this material is accurate and current, it is the user's responsibility to satisfy itself of the suitability of products for its own particular purpose. As the actual use by others is beyond our control, B2-Innovez does not provide any guarantee, implied or expressed, as to the effects of such use. No liability is accepted by B2-Innovez and/or its staff, for any loss or damage, direct or indirect, that may result from using the product, information or adopting recommendations and/or suggestions as actual conditions for use are beyond our control. This information is not to be construed as absolutely complete since additional information may be necessary or desirable for exceptional or particular circumstances.